



NEWS RELEASE

17.16 g/t Au across 9.5m

ROXMARK REPORTS CONTINUED DEFINITION OF HIGH-GRADE GOLD AT EP ZONE TARGET

Toronto, Ontario, July 29, 2009. Roxmark Mines Limited (TSXV-RMK) today announced that ongoing drilling by Premier Gold Mines Limited (TSX-PG) as operator continues to define significant high-grade gold mineralization in multiple zones at the Hardrock Project in Northwestern Ontario. The current program, consisting of delineation and exploration drilling, will continue throughout 2009 and is expected to result in an NI 43-101 compliant resource estimate by year end.

Roxmark has a 30% carried interest in the Hardrock Project which is host to several past-producing mines that collectively produced nearly 3.0 million ounces of gold primarily from relatively shallow depths (600 metres) between 1938 and 1968. Importantly, the Hardrock Project has the potential for defining several styles of mineralization capable of hosting resources, with grades and widths similar to many of Ontario's major gold mines including open pit-style mineralization with grades exceeding 1.5 g/t Au (Timmins, Hemlo), broad zones of mineralization with grades averaging 5.0+ g/t Au (Musselwhite), and narrow vein zones with higher gold grades often exceeding 7.0g/t (Red Lake, Pickle Lake). The Hardrock Project benefits from development advantages with the Trans-Canada Highway, Trans-Canada Pipeline, and major power lines running through the centre of the property.

Drilling for the balance of the year will focus on defining both open pit and underground mineralization such that the property can be moved towards advanced exploration and feasibility. Drilling at the EP Zone target continues to exceed expectations, having now intersected mineralization over a strike length of some 650 metres and to depths approaching 200 metres in the central portion of the deposit. Additionally, drilling continues to intersect mineralization in the South Porphyry Zone ("SP"), continuing to define the zone down-plunge, returning high grade gold within multiple zones. Recent highlights (some previously released) include:

- **EP Zone: 5.21 grams per tonne gold (g/t Au) across 37.0 metres (m) within the North Limb
6.51 g/t Au across 18.4 metres within the North Limb
19.03 g/t Au across 11.3 metres in step-out drilling on the South Limb**
- **SP Zone: 6.63 g/t Au across 28.1 metres within the SP Zone underground target
6.60 g/t Au across 32.6 metres within the SP Zone
36.22 g/t Au (1.06 oz/ton) across 2.2 metres within the HGV Zone target**

EP-Zone

The **EP-Zone** has been identified as a potential high-grade open pit target in the vicinity of the historic North Zone, from which 2.97 million tonnes of ore were mined at a recovered grade of 7.54 g/t Au. **Previous highlights that include 7.60 g/t Au across 20.5 m in hole EP044, 2.37 g/t Au across 62.7 m in hole EP026, 4.17 g/t Au across 29.0 m in hole EP053, 5.21 g/t Au across 37.0 m in hole EP079, and 19.03 g/t Au across**

11.3 m in hole EP080 continue to define and expand mineralization within the confines of the target pit area at EP.

The following table summarizes highlights from new assay results at the EP-Zone. A complete tabulation of results for the EP Zone can be found on Premier's website, www.premiergoldmines.com.

New Sub-Zone Intercepts within the EP Zone Target Area

Hole-ID	UTM Coordinates (m)	Dip/Azimuth (degrees)	From (m)	To (m)	Interval (m)	Grade (g/tonne)	Interval (ft)	Grade (oz/ton)	Zone
EP081	5503001 N 504815 E	-60/360	17.0	26.0	9.0	2.17	29.52	0.06	PIT
			188.5	203.5	15.0	2.76	49.2	0.08	SL
			219.0	230.0	11.0	3.66	36.08	0.11	NL
			264.5	268.0	3.5	17.94	11.5	0.52	NLB
EP082	5503000 N 504850 E	-60/360	134.1	136.5	2.4	1.66	7.9	0.05	SLB
			167.5	183.1	15.6	1.05	51.2	0.03	SL
			196.5	202.9	6.4	1.87	21.0	0.05	NL
			206.9	210.5	3.6	7.47	11.8	0.22	X
EP083	5503011 N 504903 E	-60/360	37.5	39.4	1.9	12.54	6.2	0.37	SLC
			88.5	96.0	7.5	1.66	24.6	0.05	SLB
			131.2	137.2	6.0	8.45	19.7	0.25	SL
EP084	5503095 N 504915 E	-45/360	33.5	36.8	3.3	7.93	10.8	0.23	SLB
			44.3	45.2	0.9	21.70	3.0	0.63	SL
EP085	5503162 N 504950 E	-45/180	7.3	29.8	22.5	4.15	73.8	0.12	NL
			51.0	56.0	5.0	1.32	16.4	0.04	SL
EP086	5503228 N 505050 E	-50/180	134.5	140.5	6.0	1.35	19.7	0.04	NL
EP087	5503160 N 505052 E	-45/180	15.5	33.9	18.4	6.51	60.4	0.19	NL
			45.4	46.9	1.5	3.50	4.9	0.10	SL
EP088	5503049 N 505052 E	-65/360	104.0	104.9	0.9	8.92	3.0	0.26	SL
EP089	5502999 N 505101 E	-45/360	111.0	114.0	3.0	1.60	9.8	0.05	SLB
EP090 including including	5503100 N 504099 E	-45/360	21.0	40.0	19.0	2.43	62.3	0.07	SL
			21.0	29.0	8.0	5.06	26.2	0.15	SL
			26.6	27.7	1.1	20.70	3.6	0.60	SL
EP091	5503180 N 505098 E	-45/180				NSV			
EP092	5503164 N 505149 E	-45/360				NSV			
EP093	5503001 N 504815 E	-45/360	51.0	53.0	2.0	5.30	6.6	0.15	SLC
			107.5	109.0	1.5	3.23	4.9	0.09	SL
EP094	5503124 N 505198 E	-45/360				NSV			
EP095	5503075 N 505198 E	-45/360				NSV			
EP096	5503024 N 505200 E	-45/360	115.5	118.5	3.0	1.56	9.8	0.05	SLB
			128.5	129.5	1.0	26.10	3.3	0.76	SL
EP097	5503075 N 504500 E	-45/360	109.0	110.5	1.5	7.19	4.9	0.21	SL
			118.2	120.7	2.5	3.80	8.2	0.11	NL
			154.5	161.4	6.9	1.49	22.6	0.04	NLB
			175.5	178.5	3.0	14.97	9.8	0.44	NLC
EP098 including	5503001 N 504450 E	-50/360	4.8	6.3	1.5	3.78	4.9	0.11	SLB
			38.5	40.0	1.5	6.64	4.9	0.19	SL
			211.9	251.9	40.0	1.13	131.2	0.03	NL
			241.0	245.1	4.1	3.06	13.4	0.09	NLC

EP099	5503030 N 504450 E	-50/338				NSV			
EP100	5502970 N 504450 E	-50/360	51.0	60.5	9.5	17.16	31.2	0.50	SLB
			115.5	118.5	3.0	1.96	9.8	0.06	SL
			152.0	154.5	2.5	8.20	8.2	0.24	NL
			175.0	179.5	4.5	7.94	14.8	0.23	NLB
			262.5	268.1	5.6	2.25	18.4	0.07	NLC

* True widths estimated at approximately 70% of intersection widths

SP Zone

At Hardrock, the SP Zone was partially mined in the upper levels of the mine with 264,354 tonnes (291,428 Tons) of ore mined at an average grade of 8.37g/t Au (0.244 oz/t). Intermittent historic drilling that tested the un-mined down-plunge extension of the SP Zone suggests the potential to define mineralization over a plunge length of nearly 3.0 kilometres (8,500 feet). The initial holes drilled have now intersected mineralization over a minimum plunge length of 500 metres where it remains open. **Highlights include 6.60 g/t Au across 32.6 m and 6.63 g/t Au across 28.1 m within the SP Zone, and 36.22 g/t Au across 2.2 m within the HGV Zone.**

Stephen McGibbon, P. Geo., is the Qualified Person for the information contained in this press release and is a Qualified Person within the meaning of National Instrument 43-101. Assay results are from core samples sent to Activation Laboratories, an accredited mineral analysis laboratory in Thunder Bay, Ontario, for preparation and analysis utilizing both fire assay and screen metallic methods.

About Roxmark Mines

Roxmark Mines Limited is the leader in gold and molybdenum exploration and development in the historically significant Geraldton-Beardmore area of Northwest Ontario. In addition to the Hardrock Project in the Geraldton Camp, Roxmark is pursuing a number of initiatives in the Beardmore Camp, including re-opening the Northern Empire Mine and its onsite mill and expanding the resource base at the Leitch-Sand River Mine. In recent years, Roxmark has generated cash flow from bulk-sampled gold and molybdenum processed at its fully-permitted mill and has the advantage of infrastructure from nine formerly highly productive gold mines located on its properties. These mines previously produced nearly four million ounces of gold from high-grade ore but were closed primarily due to boundary issues and dramatically lower gold prices at the time.

Further information is available on the Company's website at www.roxmark.com and on SEDAR under the Company's profile at www.sedar.com.

Forward-Looking Statements

This news release includes certain "forward-looking statements". Such forward-looking statements involve risks and uncertainties. The results or events predicted in these forward-looking statements may differ materially from actual results or events. Any forward-looking statement speaks only as of the date of this news release and, except as may be required by applicable securities laws, the Company disclaims any intent or obligation to update any forward-looking statement, whether as a result of new information, future events or results or otherwise.

Monir Younan, President
Roxmark Mines Limited
801- 80 Richmond St. West
Toronto, Ontario M5H 2A4

Tel.: (416) 860-1636
Fax: (416) 360-7355
E-mail: roxmark@on.aibn.com
Website: www.roxmark.com

Neither TSX Venture Exchange nor its Regulation Services Provider (as that term is defined in the policies of the TSX Venture Exchange) accepts responsibility for the adequacy or accuracy of this release.